



MATERIAL SAFETY DATA SHEET



1 Product and Company Identification

2 Components Hazardous

3 Health Hazard Identification

4 Emergency and First Aid

5 Fire and Explosion

6 Accidental Release Measures

7 Precautions for Handling, Storage

8 Exposure Controls and Personal Protection

9 Physical and Chemical Characteristics

10 Stability and Reactivity Data

11 Toxicological Information

12 Ecological Information

13 Disposal

14 Transportation Information

15 Regulatory Information

16 Other Information

PRODUCT AND COMPANY IDENTIFICATION

White Portland CEM II/B-LL 42.5 N –According to EN 197-1:2011
standard (Portland cement, Hydraulic Cement)

Supplier Name & Address:

Royal El Minya Cement CO., Inc.

Cairo Sheraton Airport, 7 Mustafa Refaat St,
Square No.1135 Fourth Floor, Apartment No. 7

Telephone Number for Information:

Tel.: 02 22678627 – 02 22678628

Fax Number: Fax No.: +2 02 226786

HAZARDS IDENTIFICATION

1- Classification of the substance or mixture

According to Regulation (EC) No 305 / 2011

Hazard class	Hazard category	Classification procedure
Skin irritation	2	Based on test data
Serious eye damage/ eye irritation	1	Based on test data
Skin sensitization	1B	Based on literature survey
Specific target organ toxicity single exposure respiratory tract irritation	3	Based on literature survey

Hazard statements:

H318: Causes serious eye damage

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H335: May cause respiratory irritation

According to the Directive Regulation (EC) No 305 / 2011:

- R37/38 Irritating to respiratory system and skin
- R41 Risk of serious damage to eyes
- R43 May cause sensitization by skin contact

Cement dust may cause irritation of the respiratory system.

When cement reacts with water, for instance when making concrete or mortar, or when the cement becomes damp, a strong alkaline solution is produced. Due to the high alkalinity, wet cement may provoke skin and eye irritation.

It may also cause an allergic reaction in some individuals due to the soluble Cr (VI) content.

Cement is either naturally low in soluble chromium VI or reducing agents have been added to control the levels of sensitizing soluble chromium (VI) to below 2 mg/kg (0,0002%) of the total dry weight of the cement ready for use according to legislation specified under Section 15.

2- According to regulation (EC) No 305 / 2011

- **H318:** Causes serious eye damage
- **H315:** Causes skin irritation
- **H317:** May cause an allergic skin reaction
- **H335:** May cause respiratory irritation
- **P102:** Keep out of reach of children
- **P280:** Wear protective gloves/protective clothing/eye protection/face protection
- **P305+P351+P338+P310:** If in Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, If present and easy to do. Continue rinsing. Immediately call a POISON CENTER or Doctor/physician
- **P302+P352+P333+P313:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention
- **P261+P304+P340+P312:** Avoid breathing dust/fume/gas/mist/vapors/spray.



IF INHALED: Remove victim to refresh air and keep at rest in a position comfortable for breathing. Call a Poison center or doctor/physician if you feel unwell.

- **P501:** Dispose of contents/container according to legislation

Supplemental information:

Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatitis or burns. May cause damage to products made of aluminum or other non-noble metals.2.3. **Other hazards:** Cement does not meet the criteria for PBT or VPVB in accordance with Annex XIII of REACH (Regulation (EC) No 305/2011).

EMERGENCY AND FIRST AID

White Portland cement is an odorless light white powder.

- **Eyes:** Flush immediately eye thoroughly with clean water continuously for at least 15 minutes. Consult a physician immediately if irritation persists.
- **Skin:** Affected areas must be washed with neutral soap and clean, cool water for at least 15 minutes. For reddened skin, consult a physician immediately.
- **Inhalation:** Remove exposed person to fresh air and support breathing as needed. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Consult a physician immediately if irritation persists. Inhalation of large amounts of Portland cement requires immediate medical attention.
- **Ingestion:** If the material is ingested, have the conscious person drink plenty of water or milk. Never give any thing by mouth to an unconscious or convulsing person. Consult a physician immediately.

HEALTH HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

NOTE: Potential health effects may vary depending upon the duration and degree of exposure.

EYE CONTACT: (Acute/Chronic) Exposure to airborne dust may cause immediate or delayed irritation or inflammation of the cornea. Eye contact by larger amounts of dry powder or splashes of wet Portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness.

SKIN CONTACT: Acute) Exposure to dry Portland cement may cause drying of the skin with consequent mild irritation.

(Chronic) Exposure to wet Portland cement or Dry Portland cement coming in contact with wet skin may cause more severe skin effects, including thickening, or fissuring of the skin. Prolonged exposure can cause severe skin damage in the form of chemical (caustic) burns.

(Acute/Chronic) Upon exposure to Portland cement some individuals may exhibit an allergic response ranging from a mild rash to severe skin ulcers.

INHALATION: (Acute) Exposure to Portland cement may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. Pre-existing upper respiratory and lung diseases may be aggravated by inhalation of Portland cement.

(Chronic) Inhalation exposure to free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease, and/or cause or aggravate other lung, diseases, or conditions.

INGESTION: (Acute/Chronic) Internal discomfort or ill effects are possible if large quantities are swallowed.

CARCINOGENIC POTENTIAL: Portland cement is not recognized as a carcinogen by NTP, OSHA, or IARC. However, it may contain trace amounts of heavy metals recognized as carcinogens by these organizations. Contact between cement powder and body fluids (eg sweat and eye fluids) may cause irritation, dermatitis or Burns. Cement is classified as an irritant under the Chemicals (Hazard Information and Packaging) Regulations. For further information, including control of soluble hexavalent chromium,



Hazardous Components	OSHA PEL (8-Hour TWA)	ACGIH TLV-TWA	MSHA PEL
Portland Cement (CAS #65997-15-1) 100%	5 mg respirable dust/m ³ 15 mg total dust/m ³	10 mg total dust/m ³	10 mg total dust/m ³
Calcium Sulfate (CAS #7778-18-9) [Gypsum] 5 to 7%	5 mg respirable dust/m ³ 15 mg total dust/m ³	10 mg total dust/m ³	
Magnesium Oxide (CAS #1309-48-4) 0.5 to 2%	15 mg total dust/m ³	10 mg total dust/m ³	
Crystalline Silica (CAS #14808-60-7) 0 to 0.05%	10/(% SiO ₂ + 2) mg of respirable dust/m ³ 30/(% SiO ₂ + 2) mg of total dust/m ³	0.10 mg respirable quartz/m ³	10/(% SiO ₂ + 2) mg of respirable dust/m ³ 30/(% SiO ₂ + 2) mg of total dust/m ³

FIRE AND EXPLOSION

FLASH POINT: Not Combustible

LOWER EXPLOSIVE LIMIT: None

UPPER EXPLOSIVE LIMIT: None

FLAMMABLE LIMITS: Not Applicable

EXTINGUISHING MEDIA: Not Combustible

HAZARDOUS COMBUSTION PRODUCTS: None

SPECIAL FIRE FIGHTING PROCEDURES:

- Be Aware of run off from fire control methods.
- Do not release material or waterways, as product reacts with water and becomes hard within 1 to 6 hours.
- Hardened material may clog sewers and waterways

ACCIDENTAL RELEASE MEASURES

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate protective equipment as described in section 8. Scrape up wet material and place in appropriate container. Allow material to "dry" before disposal. Do not attempt to wash masonry cement down drains. Dispose of waste material according to local, state and federal regulations.

PRECAUTIONS FOR HANDLING, STORAGE AND DISPOSAL

HANDLING AND STORAGE: Keep dry until used. Handle and store in a manner so that airborne dust does not exceed applicable exposure limits. Use adequate ventilation and dust collection.

SPILL: Use dry clean-up methods that do not disperse dust into the air or entry into surface water.

Material can be used if not contaminated. Place in an appropriate container for disposal or use.

Avoid inhalation of dust and contact with skin and eyes.

DISPOSAL: Dispose of packaging/containers according to local and state regulations for disposal of unusable or contaminated materials.

EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY PROTECTION:

- Use local exhaust or general dilution ventilation to control dust levels below applicable exposure limits.
- Minimize dispersal of dust into the air.
- When dust causes irritation or discomfort, use NIOSH approved respirators.

EYE PROTECTION:

Wear safety glasses with side shields or goggles to avoid contact with the eyes. In extremely dusty environment, wear tight-fitting unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when handling cement or cement containing products.

SKIN PROTECTION:

Wear impervious abrasion- and alkali-resistant gloves, boots, long-sleeved shirt, long pants or other protective clothing to prevent skin contact. Promptly remove clothing dusty with dry Portland cement or clothing dampened with moisture mixed with Portland cement, and launder before re-use.

PHYSICAL AND CHEMICAL CHARACTERISTICS

1-The composition of Portland limestone cement shall be as follows:

- Portland cement clinker 65.0 to 79.0 %
- Limestone 21.0 to 35.0 %
- Minor additional constituents 0.0 to 5.0 %

Advantages:

- *- Lower water demand and improved workability
- *- Lower surface laitance

2- Availability Application:

- Industrial construction facilities
- Small-size concrete products and elements
- Ready-mixed concrete made in concrete centers in compliance with BDS EN-206-1.
- Extra Rapid is available in 50kg polypropylene bags throughout Egypt.

Properties :

- Portland Limestone cement based.
- Strength CEM- II / B-LL 42.5 N
- Not Used in Concrete.

Strength Class.	Compressive Strength MPa				Initial setting time		Soundness (expansion)	
	Early Strength		Standard Strength					
	2 days	Royal results	28 days	Royal results	min	min	mm	
					Stan.	Royal	Stan.	Royal
CEM- II /B- LL 42.5 N	≤10.0	19 ± 3	≤ 42.5, R, ≤ 62.5	48.0 ± 4.0	≤ 60	150 ± 20	≤ 10.0	2.0 ± 3

Property	Test reference	Strength class	Cement type	Requirements	Royal Result
Insoluble residue	EN 196-2	42.5 N	CEM II/B-LL 42.5 N	≤ 5.0%	0.5 ± 0.2
S03	EN 196-2	42.5 N	CEM II/B-LL 42.5 N	≤3.5 %	2.7 ± 0.3
CI	EN 196-2	42.5 N	CEM II/B-LL 42.5 N	≤0.10 %	0.05 ± 0.015

APPEARANCE/ODOR:	white powder, odorless
BOILING POINT:	Not applicable
VAPOR PRESSURE:	Not applicable
PH (IN WATER) (ASTM D 1293-95)	11.90
SPECIFIC GRAVITY (H2O = 1.0):	3.00

PHYSICAL STATE:	Solid (Powder)
MELTING POINT:	Not applicable
VAPOR DENSITY:	Not applicable
SOLUBILITY IN WATER:	Slightly soluble (0.3% To 1.5%)
EVAPORATION RATE:	Not applicable

STABILITY AND REACTIVITY DATA

STABILITY: Product is stable. Keep dry until used.

CONDITIONS TO AVOID: Unintentional contact with water. Contact with water will result in hydration and produces (caustic) calcium hydroxide.

INCOMPATIBILITY: Wet Portland cement is alkaline. As such, it is incompatible with acids, ammonium salts and aluminum metal.

HAZARDOUS DECOMPOSITION: Will not occur.

HAZARDOUS POLYMERIZATION: Will not occur.

TOXICOLOGICAL INFORMATION

For a description of available, more detailed toxicological information, contact the supplier or manufacturer.

ECOLOGICAL INFORMATION

Eco toxicity: No recognized unusual toxicity to plants or animals

DISPOSAL

Dispose of waste material according to local, state and federal regulations. (Since masonry cement is stable, uncontaminated material may be saved for future use.)

Dispose of bags in approved landfill or incinerator.

TRANSPORTATION INFORMATION

Portland cement is not hazardous under Egyptian TDG regulations. (Portland cement is not regulated as per IATA.).

REGULATORY INFORMATION

1- Safety, health and environmental regulations/legislation specific for the substance or mixture

Cement is a mixture according to REACH and is not subject to registration Cement clinker is exempt from registration (Art 2.7 (b) and Annex V.10 of REACH).

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI)

1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.

2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

The so-called "Good practice guides" which contain advice on safe handling practices can be found from: <http://www.nepsi.eu/goodpractice-guide.aspx>. These good practices have been adopted under the Social Dialogue "Agreement on Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it by Employee and Employer European sectoral associations, among which CEMBUREAU.

2. Chemical safety assessment

Assessment and chemical safety report in accordance with 1907/2006 Annex I have not yet been performed.

OTHER INFORMATION

This MSDS provides information on various types of Portland cement products. A particular product's composition may vary from sample to sample. The information provided herein is believed by Royal El Minya Cement Company to be accurate at the time of preparation or prepared from sources believed to be reliable. Health and safety precautions in this data sheet may not be adequate for all individuals or situations. Users have the responsibility to comply with all laws and procedures applicable to the safe handling and use of the product, to determine the suitability of the product for its intended use, and to understand possible hazards associated with mixing Portland cement with other materials.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ROYAL ELMINYA CEMENT COMPANY.

Storage:

This product should be stored in unopened in cool conditions and should be Stacked in a safe and stable manner.

This product may be stored in either indoor or outdoor conditions.

Information On the maximum storage period can be found on the bag.

ABBREVIATIONS

- **ACGIH:** American Conference of Governmental Industrial Hygienists
- **ASTM:** American Society for Testing and Materials
- **CAS:** Chemical Abstract Service
- **CFR:** Code of Federal Regulations
- **ft³:** Cubic foot
- **IARC:** International Agency for Research on Cancer
- **m³:** Cubic meter
- **Mg:** Milligram
- **NIOSH:** National Institute for Occupational Safety and Health
- **NTP:** National Toxicology Program
- **OSHA:** Occupational Safety and Health Administration
- **PEL:** Permissible Exposure Limit
- **REL:** Recommended Exposure Limit
- **TDG:** Transportation of Dangerous Goods
- **TLV:** Threshold Limit Value
- **TSCA:** Toxic Substance Control Act
- **TWA:** Time Weighted Average
- **WHMIS:** Workplace Hazardous Materials Information System